

serie
CO
series

Luci da ponteggio Scaffold signalling lamps



Conformi alle norme
CEI 34-21 / EN 60598-1

- Plafoniera rettangolare in polietilene con diffusore rosso
- Lampadine da 24V 25W attacco E27
- Grado di protezione **IP44**
- Cavo di cablaggio tipo H05RN-F
- Distanza tra una luce e l'altra 6 Mt
- Attacco in nylon per il fissaggio a tubo "Innocenti"
- Imballo in cartone con codice a barre



- Rectangular lighting fixture made in polyethylene with red diffuser
- 24V 25W lamps E27
- Protection degree **IP44**
- Wiring cable H05RN-F
- Distance between lights 6m.
- Nylon fixing device for "Innocenti" standard tube
- Cardboard packing and bar code

Codice Articolo
Code

N. Luci
N. lights

Massima
estensione
ponteggio Mt.
Max length
scaffold Mt.

Potenza W
Power W

Pres. in uscita
Exit socket

Spina
alimentazione V
Supply plug
voltage V

€

1	CO-PL01	1	●		25		24	54,00
2	CO-PL02	2	● ●	6	50		24	88,00
3	CO-PL03	3	● ● ●	12	72	•	24	136,00
4	CO-PL05	5	● ● ● ● ●	24	125	•	24	195,00

Ricambi / Spare parts



Plafoniera
completa
Complete
ceiling light

5 CO-PL00 € 21,50




Calotta
rossa
Red
diffuser

6 CO-VTRG/R € 8,40



Gancio in nylon
per tubi innocenti
Nylon fixing device for
"Innocenti" standard
tube

7 FR-GPL € 3,00



Lampadina 25W, 24V,
attacco E27
24V 25W lamps,
E27

8 CO-LAM2524 € 3,20

serie
CO
series

Luci da ponteggio a LED LED scaffold signalling lamps

- Plafoniera con base in ABS e calotta rossa in metacrilato
- Funzionamento a LED
- Grado di protezione **IP44**
- Cavo di cablaggio tipo H05RN-F
- Distanza tra una luce e l'altra 2,5 Mt
- Attacco in nylon per il fissaggio a tubo "Innocenti"
- Imballo in cartone con codice a barre



- Lighting fixture with ABS base and metalrylic red diffuser
- LED lighting system
- Protection degree **IP44**
- Wiring cable H05RN-F
- Distance between lights 2,5m.
- Nylon fixing device for "Innocenti" standard tube
- Cardboard packing and bar code

Codice/Articolo
Code

N. Luci
N. lights

Massima
estensione
ponteggio Mt.
Max length
scaffold Mt.

Potenza W
Power W

Pres. in uscita
Exit socket

Spina
alimentazione V
Supply plug
voltage V

€

9	CO-MPL05	5	● ● ● ● ●	10	3	•	24	115,00
10	CO-MPL10	10	● ● ● ● ● ● ● ● ● ●	22,50	6	•	24	185,00
11	CO-MPL06T	6	● ● ● ● ● ●	12,50	4		220	170,00

(trasformatore incorporato con protezione elettronica
Included transformer with electronic circuit protection)

114

Ricambi / Spare parts



Microplafoniera
completa
Complete
micro-ceiling light

12 CO-MPL00 € 14,00



Calotta
rossa
Red
diffuser

13 CO-VTR/R € 2,00



Gancio in nylon
per tubi innocenti
Nylon fixing device for
"Innocenti" standard
tube

14 FR-GPL € 3,00



Scheda
a LED
LED
card

15 CO-SCH-MPL € 8,00